U.S. Serial No. 10/002,576

Reply to Office Action of: 02/28/2003

Family Number: P2001J062

Page 2 of 4

ECEIVED TO TO

Amendments To The Claims

- 1. (Currently Amended) A process for producing pearlite from an iron containing article comprising the steps of, (a) heating an iron containing article comprising at least 50 wt % iron for a time and at a temperature sufficient to convert at least a portion of said article from a ferritic structure to an austenitic structure, (b) exposing said austenitic structure, for a time sufficient and at a temperature of about 727 to about 900°C, to a carbon supersaturated CO/H₂ environment consisting essentially of CO and 10 to 50 vol% H₂, and having a carbon activity greater than about 1, to diffuse carbon into said austenitic structure and (c) cooling said iron containing article to form a continuous pearlite structure.
- 2. (Original) The process of claim I wherein said iron containing article further comprises silicon, manganese, and mixtures thereof.
 - 3. (Cancelled)
 - 4. (Cancelled)
 - 5. (Cancelled)
- 6. (Original) The process of claim 1 wherein said time sufficient to diffuse carbon into the austenitic structure ranges from about 1 minute to about 50 hours.
- 7. (Original) The process of claim 6 wherein said thickness of pearlite is at least about 10 microns.
 - 8. (Cancelled)
- 9. (Original) The process of claim I wherein the iron containing article, contains less than 0.77 wt% carbon.